

# Exhibit 2

**U.S. Patent No. 7,519,814 (“’814 Patent”)**




Accused Instrumentalities: Google’s products and services using user mode critical system elements as shared libraries, including without limitation Google Kubernetes Engine, Cloud Run, Migrate to Containers, and all versions and variations thereof since the issuance of the asserted patent.

Each Accused Instrumentality infringes the claims in substantially the same way, and the evidence shown in this chart is similarly applicable to each Accused Instrumentality. Each claim limitation is literally infringed by each Accused Instrumentality. However, to the extent any claim limitation is not met literally, it is nonetheless met under the doctrine of equivalents because the differences between the claim limitation and each Accused Instrumentality would be insubstantial, and each Accused Instrumentality performs substantially the same function, in substantially the same way, to achieve the same result as the claimed invention. Notably, Defendant has not yet articulated which, if any, particular claim limitations it believes are not met by the Accused Instrumentalities.

**Claim 1**

Claim 1	Accused Instrumentalities
<p>[1pre] 1. In a system having a plurality of servers with operating systems that differ, operating in disparate computing environments, wherein each server includes a processor and an operating system including a kernel a set of associated local system files compatible with the processor, a method of providing at least some of the servers in the system with secure, executable, applications related to a service, wherein the applications are executed in a secure environment, wherein the applications each include</p>	<p>To the extent the preamble is limiting, Google and/or its customer practices, through the Accused Instrumentalities, in a system having a plurality of servers with operating systems that differ, operating in disparate computing environments, wherein each server includes a processor and an operating system including a kernel a set of associated local system files compatible with the processor, a method of providing at least some of the servers in the system with secure, executable, applications related to a service, wherein the applications are executed in a secure environment, wherein the applications each include an object executable by at least some of the different operating systems for performing a task related to the service, as claimed.</p> <p>For example, Google Kubernetes Engine and Cloud Run, as well as containers produced by Migrate to Containers, each runs on individual servers, each of which uses an independent operating system. Google provides and/or requires that each server includes a processor with one or more cores available to the OS kernel. Google further provides and/or requires that each server has a supported operating system (<i>e.g.</i>, Container-Optimized OS, Ubuntu), which includes a kernel and associated local system files, including for example libraries such as libc/glibc, configuration files, etc. On information and belief, there exist at least two GKE/Cloud Run servers that have different operating systems, for example Container-Optimized OS and Ubuntu.</p> <p><i>See claim limitations below.</i></p>

Claim 1	Accused Instrumentalities
<p>an object executable by at least some of the different operating systems for performing a task related to the service, the method comprising:</p>	<p><i>See also, e.g.:</i></p> <p>Google Kubernetes Engine (GKE) clusters provide secured and managed Kubernetes services with autoscaling and multi-cluster support. GKE lets you deploy, manage, and scale containerized applications on Kubernetes, powered by Google Cloud.</p> <p><a href="https://cloud.google.com/migrate/containers/docs/getting-started">https://cloud.google.com/migrate/containers/docs/getting-started</a></p> <p>This page describes the node images available for Google Kubernetes Engine (GKE) nodes.</p> <p>GKE Autopilot nodes always use Container-Optimized OS with containerd ( <code>cos_containerd</code> ), which is the recommended node operating system. If you use GKE Standard, you can choose the operating system image that runs on each node during cluster or node pool creation. You can also upgrade an existing Standard cluster to use a different node image. For instructions on how to set the node image, see <a href="#">Specifying a node image</a>.</p> <p><a href="https://cloud.google.com/kubernetes-engine/docs/concepts/node-images">https://cloud.google.com/kubernetes-engine/docs/concepts/node-images</a></p>

Claim 1	Accused Instrumentalities								
	<p>GKE offers the following node image options per OS for your cluster:</p> <table border="1"> <thead> <tr> <th data-bbox="657 342 701 370">OS</th><th data-bbox="842 342 982 370">Node images</th></tr> </thead> <tbody> <tr> <td data-bbox="657 415 779 509">Container-Optimized OS</td><td data-bbox="842 415 1843 623"> <ul style="list-style-type: none"> <li>Container-Optimized OS with containerd (<a href="#">cos_containerd</a>) <ul style="list-style-type: none"> <li>★ GKE Autopilot clusters always use this image.</li> </ul> </li> <li>Container-Optimized OS with Docker (<a href="#">cos</a>) (Unsupported in GKE version 1.24 and later)</li> </ul> </td></tr> <tr> <td data-bbox="657 656 743 680">Ubuntu</td><td data-bbox="842 656 1843 737"> <ul style="list-style-type: none"> <li>Ubuntu with containerd (<a href="#">ubuntu_containerd</a>)</li> <li>Ubuntu with Docker (<a href="#">ubuntu</a>) (Unsupported in GKE version 1.24 and later)</li> </ul> </td></tr> <tr> <td data-bbox="657 769 768 834">Windows Server</td><td data-bbox="842 769 1843 1297"> <ul style="list-style-type: none"> <li>Windows Server LTSC with containerd (<a href="#">windows_ltsc_containerd</a>) (Supports both LTSC2022 and LTSC2019 node images)</li> <li>Windows Server LTSC with Docker (<a href="#">windows_ltsc</a>) (Unsupported in GKE version 1.24 and later. Unsupported for Windows Server LTSC2022.)</li> </ul> <div>  <b>Warning:</b> Windows Server Semi-Annual Channel (SAC) images aren't supported after August 9, 2022 because Microsoft is removing support for the SAC. For potential impact and migration instructions, refer to <a href="#">Windows Server Semi-Annual Channel end of servicing</a>. </div> <ul style="list-style-type: none"> <li>Windows Server SAC with containerd (<a href="#">windows_sac_containerd</a>)</li> <li>Windows Server SAC with Docker (<a href="#">windows_sac</a>) (Unsupported in GKE version 1.24 and later)</li> </ul> </td></tr> </tbody> </table> <p><a href="https://cloud.google.com/kubernetes-engine/docs/concepts/node-images">https://cloud.google.com/kubernetes-engine/docs/concepts/node-images</a></p>	OS	Node images	Container-Optimized OS	<ul style="list-style-type: none"> <li>Container-Optimized OS with containerd (<a href="#">cos_containerd</a>) <ul style="list-style-type: none"> <li>★ GKE Autopilot clusters always use this image.</li> </ul> </li> <li>Container-Optimized OS with Docker (<a href="#">cos</a>) (Unsupported in GKE version 1.24 and later)</li> </ul>	Ubuntu	<ul style="list-style-type: none"> <li>Ubuntu with containerd (<a href="#">ubuntu_containerd</a>)</li> <li>Ubuntu with Docker (<a href="#">ubuntu</a>) (Unsupported in GKE version 1.24 and later)</li> </ul>	Windows Server	<ul style="list-style-type: none"> <li>Windows Server LTSC with containerd (<a href="#">windows_ltsc_containerd</a>) (Supports both LTSC2022 and LTSC2019 node images)</li> <li>Windows Server LTSC with Docker (<a href="#">windows_ltsc</a>) (Unsupported in GKE version 1.24 and later. Unsupported for Windows Server LTSC2022.)</li> </ul> <div>  <b>Warning:</b> Windows Server Semi-Annual Channel (SAC) images aren't supported after August 9, 2022 because Microsoft is removing support for the SAC. For potential impact and migration instructions, refer to <a href="#">Windows Server Semi-Annual Channel end of servicing</a>. </div> <ul style="list-style-type: none"> <li>Windows Server SAC with containerd (<a href="#">windows_sac_containerd</a>)</li> <li>Windows Server SAC with Docker (<a href="#">windows_sac</a>) (Unsupported in GKE version 1.24 and later)</li> </ul>
OS	Node images								
Container-Optimized OS	<ul style="list-style-type: none"> <li>Container-Optimized OS with containerd (<a href="#">cos_containerd</a>) <ul style="list-style-type: none"> <li>★ GKE Autopilot clusters always use this image.</li> </ul> </li> <li>Container-Optimized OS with Docker (<a href="#">cos</a>) (Unsupported in GKE version 1.24 and later)</li> </ul>								
Ubuntu	<ul style="list-style-type: none"> <li>Ubuntu with containerd (<a href="#">ubuntu_containerd</a>)</li> <li>Ubuntu with Docker (<a href="#">ubuntu</a>) (Unsupported in GKE version 1.24 and later)</li> </ul>								
Windows Server	<ul style="list-style-type: none"> <li>Windows Server LTSC with containerd (<a href="#">windows_ltsc_containerd</a>) (Supports both LTSC2022 and LTSC2019 node images)</li> <li>Windows Server LTSC with Docker (<a href="#">windows_ltsc</a>) (Unsupported in GKE version 1.24 and later. Unsupported for Windows Server LTSC2022.)</li> </ul> <div>  <b>Warning:</b> Windows Server Semi-Annual Channel (SAC) images aren't supported after August 9, 2022 because Microsoft is removing support for the SAC. For potential impact and migration instructions, refer to <a href="#">Windows Server Semi-Annual Channel end of servicing</a>. </div> <ul style="list-style-type: none"> <li>Windows Server SAC with containerd (<a href="#">windows_sac_containerd</a>)</li> <li>Windows Server SAC with Docker (<a href="#">windows_sac</a>) (Unsupported in GKE version 1.24 and later)</li> </ul>								

Claim 1	Accused Instrumentalities																		
	<p>Use Migrate to Containers to modernize traditional applications away from virtual machine (VM) instances and into native containers that run on Google Kubernetes Engine (GKE), Anthos clusters, or Cloud Run platform. You can migrate workloads from VMs that run on VMware or Compute Engine, giving you the flexibility to containerize your existing workloads with ease.</p> <p><a href="https://cloud.google.com/migrate/containers/docs/getting-started">https://cloud.google.com/migrate/containers/docs/getting-started</a></p> <p>Given that, using tools like <a href="#">Migrate to Containers</a> is a uniquely smart, efficient way to modernize traditional applications away from virtual machines and into native containers. Our unique automation approach extracts critical application elements from a VM so you can easily insert those elements into containers running on <a href="#">Google Kubernetes Engine</a> (GKE), <b>without</b> artifacts like guest OS layers that VMs need but that are unnecessary for containers.</p> <p><a href="https://cloud.google.com/blog/products/containers-kubernetes/how-migrate-for-anthos-improves-vm-to-container-migration">https://cloud.google.com/blog/products/containers-kubernetes/how-migrate-for-anthos-improves-vm-to-container-migration</a></p> <p>Migrate to Containers supports migrations of VMs to containers on Google Kubernetes Engine on the 64-bit Linux operating systems listed in the following table.</p> <table><tr><th>OS</th><th>Compute Engine</th><th>VMware</th></tr><tr><td>CentOS</td><td>6.0, 7.0, 7.0 UEFI, 8.0</td><td>6.7, 6.9, 7.6</td></tr><tr><td>Debian</td><td>7.0, 8.0, 9.0, 10.0</td><td>9.4, 9.6</td></tr><tr><td>RHEL</td><td>6.0, 7.0, 7.0 UEFI, 7.4 SAP, 7.6 SAP, 8.0</td><td>6.5, 7.5, 7.6, 8.3</td></tr><tr><td>SUSE</td><td>12, 12 SP3 SAP, 12 SP4 SAP, 15, 15 SAP, 15 SP1 SAP</td><td>12 SP2, 12 SP3, 12 SP4, 15</td></tr><tr><td>Ubuntu</td><td>12 LTS, 14 LTS, 16 LTS, 16 LTS minimal, 18 LTS, 18 LTS minimal, 18 LTS UEFI, 19.04, 19.04 minimal</td><td>12.04.5 LTS, 14.04 LTS, 16.04 LTS, 18.04.10 LTS</td></tr></table> <p><a href="https://cloud.google.com/migrate/containers/docs/compatible-os-versions">https://cloud.google.com/migrate/containers/docs/compatible-os-versions</a>, Last accessed on June 05, 2023</p>	OS	Compute Engine	VMware	CentOS	6.0, 7.0, 7.0 UEFI, 8.0	6.7, 6.9, 7.6	Debian	7.0, 8.0, 9.0, 10.0	9.4, 9.6	RHEL	6.0, 7.0, 7.0 UEFI, 7.4 SAP, 7.6 SAP, 8.0	6.5, 7.5, 7.6, 8.3	SUSE	12, 12 SP3 SAP, 12 SP4 SAP, 15, 15 SAP, 15 SP1 SAP	12 SP2, 12 SP3, 12 SP4, 15	Ubuntu	12 LTS, 14 LTS, 16 LTS, 16 LTS minimal, 18 LTS, 18 LTS minimal, 18 LTS UEFI, 19.04, 19.04 minimal	12.04.5 LTS, 14.04 LTS, 16.04 LTS, 18.04.10 LTS
OS	Compute Engine	VMware																	
CentOS	6.0, 7.0, 7.0 UEFI, 8.0	6.7, 6.9, 7.6																	
Debian	7.0, 8.0, 9.0, 10.0	9.4, 9.6																	
RHEL	6.0, 7.0, 7.0 UEFI, 7.4 SAP, 7.6 SAP, 8.0	6.5, 7.5, 7.6, 8.3																	
SUSE	12, 12 SP3 SAP, 12 SP4 SAP, 15, 15 SAP, 15 SP1 SAP	12 SP2, 12 SP3, 12 SP4, 15																	
Ubuntu	12 LTS, 14 LTS, 16 LTS, 16 LTS minimal, 18 LTS, 18 LTS minimal, 18 LTS UEFI, 19.04, 19.04 minimal	12.04.5 LTS, 14.04 LTS, 16.04 LTS, 18.04.10 LTS																	

Claim 1	Accused Instrumentalities
	<p>Containers can run virtually anywhere, greatly easing development and deployment: on Linux, Windows, and Mac operating systems; on virtual machines or on physical servers; on a developer's machine or in data centers on-premises; and of course, in the public cloud.</p> <p><a href="https://cloud.google.com/learn/what-are-containers">https://cloud.google.com/learn/what-are-containers</a></p> <p>A container is a way of packaging a given application's code and dependencies so that the application will run easily in any computing environment. This solves the common problem of</p> <p><a href="https://services.google.com/fh/files/misc/why_container_security_matters.pdf">https://services.google.com/fh/files/misc/why_container_security_matters.pdf</a></p>

Claim 1	Accused Instrumentalities
	<div data-bbox="640 240 1381 646"> <p>The diagram compares two system architectures. On the left, the 'Source Machine' shows a stack: File system (with a disk icon) at the base, followed by OS Kernel + drivers, then a layer with Logging, Tomcat server, and Other apps. Above this are Services, App 1, App 2 (highlighted in yellow), App 3, and another Services layer. On the right, the 'Google containers platform' shows a stack: OS Kernel + drivers at the base, followed by Logging, Networking, and Persistent volume. Above these is a 'Flexible deployment' box containing a 'Container image' (with App 2, Tomcat, and Services) and another Persistent volume. A blue arrow points from App 2 in the Source Machine to the Container image in the Google containers platform.</p> </div> <p><a href="https://cloud.google.com/blog/products/application-modernization/shift-your-apps-to-container-based-workloads-on-the-command-line">https://cloud.google.com/blog/products/application-modernization/shift-your-apps-to-container-based-workloads-on-the-command-line</a></p> <div data-bbox="640 755 1150 1149"> <p>This diagram shows a container architecture stack. At the top are three application boxes: App 1 (green), App 2 (yellow), and App 3 (pink). Below each app is a corresponding 'Bins/Libs' box of the same color. These sit on a blue 'Container Runtime' bar, which is on top of a light gray 'Host Operating System' bar. Below the OS is a dark gray 'Infrastructure' bar. The entire stack is labeled 'Containers' at the bottom.</p> </div> <p><a href="https://services.google.com/fh/files/misc/why_container_security_matters.pdf">https://services.google.com/fh/files/misc/why_container_security_matters.pdf</a></p>


Claim 1	Accused Instrumentalities
	<p>Containers virtualize CPU, memory, storage, and network resources at the operating system level, providing developers with a view of the OS logically isolated from other applications.</p> <p><a href="https://cloud.google.com/learn/what-are-containers">https://cloud.google.com/learn/what-are-containers</a></p> <p>Containers are much more lightweight than VMs</p> <p>Containers virtualize at the OS level while VMs virtualize at the hardware level</p> <p>Containers share the OS kernel and use a fraction of the memory VMs require</p> <p><a href="https://cloud.google.com/learn/what-are-containers">https://cloud.google.com/learn/what-are-containers</a></p> <p>Containers use specific features of the Linux kernel that “trick” individual applications into thinking they’re in their own unique environment, even though multiple applications share the same host kernel. (If you’re not familiar with the Linux kernel, it’s a part of the operating system that communicates between processes--requests that do user tasks like opening a file, running a program-- and the hardware. It manages resources like memory and CPU to meet these requests).</p> <p><a href="https://services.google.com/fh/files/misc/why_container_security_matters.pdf">https://services.google.com/fh/files/misc/why_container_security_matters.pdf</a></p> <p>The core components of the Linux kernel that are used for containers are <b>cgroups</b> – control groups, which define the resources like CPU and memory which are available to a given process – and <b>namespaces</b>, which are a way of separating processes by restricting what each process can see, so that system resources “appear” isolated to the process.</p> <p><a href="https://services.google.com/fh/files/misc/why_container_security_matters.pdf">https://services.google.com/fh/files/misc/why_container_security_matters.pdf</a></p>
[1a] storing in memory accessible to at least some of the servers a plurality of secure containers of application	The method practiced by Google and/or its customer through the Accused Instrumentalities includes a step of storing in memory accessible to at least some of the servers a plurality of secure containers of application software, each container comprising one or more of the executable applications and a



Claim 1	Accused Instrumentalities
<p>software, each container comprising one or more of the executable applications and a set of associated system files required to execute the one or more applications, for use with a local kernel residing permanently on one of the servers;</p>	<p>set of associated system files required to execute the one or more applications, for use with a local kernel residing permanently on one of the servers.</p> <p>For example, GKE, Cloud Run, and Migrate to Containers each stores application containers, sometimes called Docker containers, container images, Kubernetes containers, or Kubernetes pods, in persistent storage available to each node running the application. The container might be in a format defined by the Open Container Initiative. This storage may be physically attached to the server or connected through any supported interconnect, including over a network. Each container includes the application software as well as a Linux user space required to execute the application, for example libc/glibc and other shared libraries, configuration files, etc. necessary for the application. For example, the container includes a base OS image, provided by Google or by a third party, such as a Debian, Rocky Linux, or Ubuntu base image. The container is compatible with the host kernel, for example because the container libraries are linked against the Linux kernel, and the supported host operating systems also use the Linux kernel, which has a stable binary interface.</p> <p>For another example, GKE and Cloud Run each stores files, pertaining to the applications, in ephemeral or persistent volumes, required to execute the applications within those containers. Because these volumes are stored and accessible within the GKE/Cloud Run environment, it is inferred that they are stored in the memory of the server as claimed.</p> <p><i>See, e.g.:</i></p>

Claim 1	Accused Instrumentalities
	<p data-bbox="657 253 1104 297">What are base images?</p> <p data-bbox="657 354 1875 467">A base image is the starting point for most container-based development workflows. Developers start with a base image and layer on top of it the necessary libraries, binaries, and configuration files used to run their application.</p> <p data-bbox="657 509 1885 667">Many base images are basic or minimal Linux distributions: Debian, Ubuntu, Red Hat Enterprise Linux (RHEL), Rocky Linux, or Alpine. Developers can consume these images directly from Docker Hub or other sources. There are official providers along with a wide variety of other downstream repackagers that layer software to meet customer needs.</p> <p data-bbox="657 709 1885 823">Google maintains base images for building its own applications. These images are built from the same source that Docker Hub uses. Therefore, they match the images you would get from Docker Hub.</p> <p data-bbox="657 865 1843 940">The advantage of using Google-maintained images is that they are stored on Google Cloud, so you can pull these images directly from your environment without having to traverse networks.</p> <p data-bbox="657 982 1864 1057">Google updates these images whenever a new version of an official image is released. For more information on image versions, see the GitHub repository of <a data-bbox="1423 1024 1608 1057" href="#">official images</a>.</p> <p data-bbox="634 1081 1589 1114"><a data-bbox="634 1081 1589 1114" href="https://cloud.google.com/software-supply-chain-security/docs/base-images">https://cloud.google.com/software-supply-chain-security/docs/base-images</a></p>

Claim 1	Accused Instrumentalities																											
	<h2>Google-provided base images</h2> <p>Google-provided <a href="#">base images</a> are available for the following OS distributions:</p> <table><tr><th>OS</th><th>Repository path</th><th>Google Cloud Marketplace listing</th></tr><tr><td>Debian 10 "Buster"</td><td><a href="https://marketplace.gcr.io/google/debian10">marketplace.gcr.io/google/debian10</a></td><td><a href="#">Google Cloud Marketplace</a></td></tr><tr><td>Debian 11 "Bullseye"</td><td><a href="https://marketplace.gcr.io/google/debian11">marketplace.gcr.io/google/debian11</a></td><td><a href="#">Google Cloud Marketplace</a></td></tr><tr><td>Debian 12 "Bookworm"</td><td><a href="https://marketplace.gcr.io/google/debian12">marketplace.gcr.io/google/debian12</a></td><td><a href="#">Google Cloud Marketplace</a></td></tr><tr><td>Rocky Linux 8</td><td><a href="https://marketplace.gcr.io/google/rockylinux8">marketplace.gcr.io/google/rockylinux8</a></td><td><a href="#">Google Cloud Marketplace</a></td></tr><tr><td>Rocky Linux 9</td><td><a href="https://marketplace.gcr.io/google/rockylinux9">marketplace.gcr.io/google/rockylinux9</a></td><td><a href="#">Google Cloud Marketplace</a></td></tr><tr><td>Ubuntu 20.04</td><td><a href="https://marketplace.gcr.io/google/ubuntu2004">marketplace.gcr.io/google/ubuntu2004</a></td><td><a href="#">Google Cloud Marketplace</a></td></tr><tr><td>Ubuntu 22.04</td><td><a href="https://marketplace.gcr.io/google/ubuntu2204">marketplace.gcr.io/google/ubuntu2204</a></td><td><a href="#">Google Cloud Marketplace</a></td></tr><tr><td>Ubuntu 24.04</td><td><a href="https://marketplace.gcr.io/google/ubuntu2404">marketplace.gcr.io/google/ubuntu2404</a></td><td><a href="#">Google Cloud Marketplace</a></td></tr></table> <p><a href="https://cloud.google.com/software-supply-chain-security/docs/base-images">https://cloud.google.com/software-supply-chain-security/docs/base-images</a></p>	OS	Repository path	Google Cloud Marketplace listing	Debian 10 "Buster"	<a href="https://marketplace.gcr.io/google/debian10">marketplace.gcr.io/google/debian10</a>	<a href="#">Google Cloud Marketplace</a>	Debian 11 "Bullseye"	<a href="https://marketplace.gcr.io/google/debian11">marketplace.gcr.io/google/debian11</a>	<a href="#">Google Cloud Marketplace</a>	Debian 12 "Bookworm"	<a href="https://marketplace.gcr.io/google/debian12">marketplace.gcr.io/google/debian12</a>	<a href="#">Google Cloud Marketplace</a>	Rocky Linux 8	<a href="https://marketplace.gcr.io/google/rockylinux8">marketplace.gcr.io/google/rockylinux8</a>	<a href="#">Google Cloud Marketplace</a>	Rocky Linux 9	<a href="https://marketplace.gcr.io/google/rockylinux9">marketplace.gcr.io/google/rockylinux9</a>	<a href="#">Google Cloud Marketplace</a>	Ubuntu 20.04	<a href="https://marketplace.gcr.io/google/ubuntu2004">marketplace.gcr.io/google/ubuntu2004</a>	<a href="#">Google Cloud Marketplace</a>	Ubuntu 22.04	<a href="https://marketplace.gcr.io/google/ubuntu2204">marketplace.gcr.io/google/ubuntu2204</a>	<a href="#">Google Cloud Marketplace</a>	Ubuntu 24.04	<a href="https://marketplace.gcr.io/google/ubuntu2404">marketplace.gcr.io/google/ubuntu2404</a>	<a href="#">Google Cloud Marketplace</a>
OS	Repository path	Google Cloud Marketplace listing																										
Debian 10 "Buster"	<a href="https://marketplace.gcr.io/google/debian10">marketplace.gcr.io/google/debian10</a>	<a href="#">Google Cloud Marketplace</a>																										
Debian 11 "Bullseye"	<a href="https://marketplace.gcr.io/google/debian11">marketplace.gcr.io/google/debian11</a>	<a href="#">Google Cloud Marketplace</a>																										
Debian 12 "Bookworm"	<a href="https://marketplace.gcr.io/google/debian12">marketplace.gcr.io/google/debian12</a>	<a href="#">Google Cloud Marketplace</a>																										
Rocky Linux 8	<a href="https://marketplace.gcr.io/google/rockylinux8">marketplace.gcr.io/google/rockylinux8</a>	<a href="#">Google Cloud Marketplace</a>																										
Rocky Linux 9	<a href="https://marketplace.gcr.io/google/rockylinux9">marketplace.gcr.io/google/rockylinux9</a>	<a href="#">Google Cloud Marketplace</a>																										
Ubuntu 20.04	<a href="https://marketplace.gcr.io/google/ubuntu2004">marketplace.gcr.io/google/ubuntu2004</a>	<a href="#">Google Cloud Marketplace</a>																										
Ubuntu 22.04	<a href="https://marketplace.gcr.io/google/ubuntu2204">marketplace.gcr.io/google/ubuntu2204</a>	<a href="#">Google Cloud Marketplace</a>																										
Ubuntu 24.04	<a href="https://marketplace.gcr.io/google/ubuntu2404">marketplace.gcr.io/google/ubuntu2404</a>	<a href="#">Google Cloud Marketplace</a>																										

Claim 1	Accused Instrumentalities
	<p>There are several storage options for applications running on Google Kubernetes Engine (GKE). The choices vary in terms of</p> <p>Volumes are a storage unit accessible to containers in a Pod. Some volume types are backed by ephemeral storage. Ephemeral storage types (for example, <a href="#">emptyDir</a> ) do not persist after the Pod ceases to exist. These types are useful for scratch space for applications. You can <a href="#">manage your local ephemeral storage resources</a> as you do your CPU and memory resources. Other volume types are backed by durable storage.</p> <p><a href="https://cloud.google.com/kubernetes-engine/docs/concepts/storage-overview">https://cloud.google.com/kubernetes-engine/docs/concepts/storage-overview</a></p> <p>6. Do Docker containers package up the entire OS and make it easier to deploy?</p> <p>Docker containers do not package up the OS. They package up the applications with everything that the application needs to run. The engine is installed on top of the OS running on a host. Containers share the OS kernel allowing a single host to run multiple containers.</p> <p><a href="https://www.docker.com/blog/the-10-most-common-questions-it-admins-ask-about-docker/">https://www.docker.com/blog/the-10-most-common-questions-it-admins-ask-about-docker/</a></p> <p>At its core, a volume is a directory, possibly with some data in it, which is accessible to the containers in a pod. How that directory comes to be, the</p> <p><code>.spec.containers[*].volumeMounts</code> . A process in a container sees a filesystem view composed from the initial contents of the <u>container image</u>, plus volumes (if defined) mounted inside the container. The process sees a root filesystem that initially matches the contents of the container image. Any writes to within that filesystem hierarchy, if allowed, affect what that process views when it performs a subsequent filesystem access. Volumes mount at the <a href="#">specified paths</a> within the image. For each container defined within a Pod, you must independently specify where to mount each volume that the container uses.</p> <p><a href="https://kubernetes.io/docs/concepts/storage/volumes/">https://kubernetes.io/docs/concepts/storage/volumes/</a></p>


Claim 1	Accused Instrumentalities
	<div data-bbox="640 240 1381 646"> <p>The diagram illustrates the transition of application components from a traditional source machine to a containerized environment. On the left, the 'Source Machine' shows a stack: File system (with a database icon), OS Kernel + drivers, Tomcat server (with Logging), and a row of Services, App 1, App 2, App 3, and Other apps. On the right, the 'Google containers platform' shows a similar stack: OS Kernel + drivers, Logging, Networking, Persistent volume, Services, Tomcat, and App 2. A 'Flexible deployment' box encloses the Container image (App 2, Tomcat, Services) and Persistent volume layers. Blue arrows indicate the migration of App 2 and its dependencies from the source machine to the container image.</p> </div> <p><a href="https://cloud.google.com/blog/products/application-modernization/shift-your-apps-to-container-based-workloads-on-the-command-line">https://cloud.google.com/blog/products/application-modernization/shift-your-apps-to-container-based-workloads-on-the-command-line</a></p> <p>A container is a way of packaging a given application's code and dependencies so that the application will run easily in any computing environment. This solves the common problem of</p> <p>The container image specifies the container's file system. For example, if you're running a Node.js application, the container image would contain your app, Node.js, and other dependencies like Linux system libraries (except the kernel). A container image usually extends a base operating system image, or <b>base image</b>. This base image is the basis of your container, so you'll want to ensure that it's properly patched and free from known vulnerabilities.</p>

Claim 1	Accused Instrumentalities
	<p>workloads onto each server. As such, the architecture of containers means that they're deployed with multiple containers sharing the same kernel.</p> <p><a href="https://services.google.com/fh/files/misc/why_container_security_matters.pdf">https://services.google.com/fh/files/misc/why_container_security_matters.pdf</a></p> <p>Containers are lightweight packages of your application code together with dependencies such as specific versions of programming language runtimes and libraries required to run your software services.</p> <p><a href="https://cloud.google.com/learn/what-are-containers">https://cloud.google.com/learn/what-are-containers</a></p>

Claim 1	Accused Instrumentalities
	<h2 data-bbox="646 248 1272 316">About storage drivers</h2> <p data-bbox="646 362 1871 488">To use storage drivers effectively, it's important to know how Docker builds and stores images, and how these images are used by containers. You can use this information to make informed choices about the best way to persist data from your applications and avoid performance problems along the way.</p> <h2 data-bbox="646 557 1564 613">Storage drivers versus Docker volumes</h2> <p data-bbox="646 651 1913 919">Docker uses storage drivers to store image layers, and to store data in the writable layer of a container. The container's writable layer doesn't persist after the container is deleted, but is suitable for storing ephemeral data that is generated at runtime. Storage drivers are optimized for space efficiency, but (depending on the storage driver) write speeds are lower than native file system performance, especially for storage drivers that use a copy-on-write filesystem. Write-intensive applications, such as database storage, are impacted by a performance overhead, particularly if pre-existing data exists in the read-only layer.</p> <p data-bbox="646 967 1906 1094">Use Docker volumes for write-intensive data, data that must persist beyond the container's lifespan, and data that must be shared between containers. Refer to the <a data-bbox="1339 1016 1535 1044" href="#">volumes section</a> to learn how to use volumes to persist data and improve performance.</p> <p data-bbox="636 1122 1226 1154"><a data-bbox="636 1122 1226 1154" href="https://docs.docker.com/storage/storagedriver/">https://docs.docker.com/storage/storagedriver/</a></p>

Claim 1	Accused Instrumentalities
	<h2 data-bbox="657 245 1081 302">Images and layers</h2> <p data-bbox="657 337 1822 415">A Docker image is built up from a series of layers. Each layer represents an instruction in the image's Dockerfile. Each layer except the very last one is read-only. Consider the following Dockerfile:</p> <pre data-bbox="674 483 1453 797"> # syntax=docker/dockerfile:1  FROM ubuntu:22.04 LABEL org.opencontainers.image.authors="org@example.com" COPY . /app RUN make /app RUN rm -r \$HOME/.cache CMD python /app/app.py </pre> <p data-bbox="657 862 1900 1170">This Dockerfile contains four commands. Commands that modify the filesystem create a layer. The <code>FROM</code> statement starts out by creating a layer from the <code>ubuntu:22.04</code> image. The <code>LABEL</code> command only modifies the image's metadata, and doesn't produce a new layer. The <code>COPY</code> command adds some files from your Docker client's current directory. The first <code>RUN</code> command builds your application using the <code>make</code> command, and writes the result to a new layer. The second <code>RUN</code> command removes a cache directory, and writes the result to a new layer. Finally, the <code>CMD</code> instruction specifies what command to run within the container, which only modifies the image's metadata, which doesn't produce an image layer.</p> <p data-bbox="634 1192 1226 1224"><a href="https://docs.docker.com/storage/storagedriver/">https://docs.docker.com/storage/storagedriver/</a></p>




Claim 1	Accused Instrumentalities
	<p>Each layer is only a set of differences from the layer before it. Note that both <i>adding</i>, and <i>removing</i> files will result in a new layer. In the example above, the <code>\$HOME/.cache</code> directory is removed, but will still be available in the previous layer and add up to the image's total size. Refer to the <a href="#">Best practices for writing Dockerfiles</a> and <a href="#">use multi-stage builds</a> sections to learn how to optimize your Dockerfiles for efficient images.</p> <p>The layers are stacked on top of each other. When you create a new container, you add a new writable layer on top of the underlying layers. This layer is often called the "container layer". All changes made to the running container, such as writing new files, modifying existing files, and deleting files, are written to this thin writable container layer. The diagram below shows a container based on an <code>ubuntu:15.04</code> image.</p>  <p>The diagram illustrates the layer architecture of a Docker container. It shows a stack of four image layers, each represented by a blue rectangle with a hash and a size. From bottom to top, the layers are: <code>d3a1f33e8a5a</code> (188.1 MB), <code>c22013c84729</code> (194.5 KB), <code>d74508fb6632</code> (1.895 KB), and <code>91e54dfb1179</code> (0 B). These layers are collectively labeled as 'Image Layers (R/O)' with a padlock icon indicating they are read-only. Above this stack is a dashed box labeled 'Thin R/W layer', which is also labeled as the 'Container layer'. Arrows indicate the relationship between the container layer and the image layers. The entire stack is labeled 'Container (based on ubuntu:15.04 image)'.</p> <p><a href="https://docs.docker.com/storage/storagedriver/">https://docs.docker.com/storage/storagedriver/</a></p>

Claim 1	Accused Instrumentalities
	<h2 data-bbox="653 256 919 321">Volumes</h2> <p data-bbox="653 375 1906 505">Volumes are the preferred mechanism for persisting data generated by and used by Docker containers. While <a href="#">bind mounts</a> are dependent on the directory structure and OS of the host machine, volumes are completely managed by Docker. Volumes have several advantages over bind mounts:</p> <p data-bbox="634 526 1308 558"><a href="https://kubernetes.io/docs/concepts/storage/volumes/">https://kubernetes.io/docs/concepts/storage/volumes/</a></p> <h2 data-bbox="653 610 1226 659">Container environment</h2> <p data-bbox="653 696 1474 764">The Kubernetes Container environment provides several important resources to Containers:</p> <ul data-bbox="695 802 1451 964" style="list-style-type: none"><li>• A filesystem, which is a combination of an <a href="#">image</a> and one or more <a href="#">volumes</a>.</li><li>• Information about the Container itself.</li><li>• Information about other objects in the cluster.</li></ul> <p data-bbox="634 997 1528 1029"><a href="https://kubernetes.io/docs/concepts/containers/container-environment/">https://kubernetes.io/docs/concepts/containers/container-environment/</a></p>

Claim 1	Accused Instrumentalities
	<h2 data-bbox="659 250 877 315">Images</h2> <p data-bbox="659 347 1520 500">A container image represents binary data that encapsulates an application and all its software dependencies. Container images are executable software bundles that can run standalone and that make very well defined assumptions about their runtime environment.</p> <p data-bbox="659 535 1528 607">You typically create a container image of your application and push it to a registry before referring to it in a <u>Pod</u>.</p> <p data-bbox="634 636 1327 669"><a href="https://kubernetes.io/docs/concepts/containers/images/">https://kubernetes.io/docs/concepts/containers/images/</a></p> <h2 data-bbox="653 711 919 769">Volumes</h2> <p data-bbox="653 808 1482 880">On-disk files in a container are ephemeral, which presents some problems for non-trivial applications when running in containers.</p> <p data-bbox="653 889 1428 922">One problem occurs when a container crashes or is stopped.</p> <p data-bbox="653 932 1528 1253">Container state is not saved so all of the files that were created or modified during the lifetime of the container are lost. During a crash, kubelet restarts the container with a clean state. Another problem occurs when multiple containers are running in a <u>Pod</u> and need to share files. It can be challenging to setup and access a shared filesystem across all of the containers. The Kubernetes <u>volume</u> abstraction solves both of these problems. Familiarity with <u>Pods</u> is suggested.</p> <p data-bbox="634 1279 1306 1312"><a href="https://kubernetes.io/docs/concepts/storage/volumes/">https://kubernetes.io/docs/concepts/storage/volumes/</a></p>

Claim 1	Accused Instrumentalities
	<div data-bbox="659 253 1299 315"><h2>Open Container Initiative</h2><hr/></div> <div data-bbox="659 375 1186 423"><h3>Image Format Specification</h3><hr/></div> <div data-bbox="659 467 1904 547"><p>This specification defines an OCI Image, consisting of an <a href="#">image manifest</a>, an <a href="#">image index</a> (optional), a set of <a href="#">filesystem layers</a>, and a <a href="#">configuration</a>.</p></div> <div data-bbox="659 576 1908 656"><p>The goal of this specification is to enable the creation of interoperable tools for building, transporting, and preparing a container image to run.</p></div> <div data-bbox="625 678 1482 753"><p><a href="https://github.com/opencontainers/image-spec/blob/a6af2b480dcfc001ba975f44de53001c873cb0ef/spec.md">https://github.com/opencontainers/image-spec/blob/a6af2b480dcfc001ba975f44de53001c873cb0ef/spec.md</a></p></div>

Claim 1	Accused Instrumentalities
	<p data-bbox="648 250 831 289"><b>Overview</b></p> <p data-bbox="648 345 1892 586">At a high level the image manifest contains metadata about the contents and dependencies of the image including the content-addressable identity of one or more <a href="#">filesystem layer changeset</a> archives that will be unpacked to make up the final runnable filesystem. The image configuration includes information such as application arguments, environments, etc. The image index is a higher-level manifest which points to a list of manifests and descriptors. Typically, these manifests may provide different implementations of the image, possibly varying by platform or other attributes.</p> <div data-bbox="648 626 1906 1008">  <p>The diagram shows the relationship between a code snippet, a layer, an image index, and a configuration. On the left, a code snippet for a 'HelloWorld' class is shown. An arrow points from this code to a cylinder labeled 'layer' which contains the paths '/bin/java', '/opt/app.jar', and '/lib/libc'. To the right of the layer is a plus sign, followed by a document icon labeled 'image index' containing a JSON snippet with 'manifests' and 'platform' fields. Another plus sign follows, then a document icon labeled 'config' containing a JSON snippet with 'config' and 'Cmd' fields. Each of these three components (layer, image index, and config) has a small square icon with the letters 'Ci' in the top-left corner.</p> <pre data-bbox="674 764 982 857"> public class HelloWorld {     public static void main(String[] args) {         System.out.println("Hello, World");     } } </pre> <pre data-bbox="1121 776 1283 857"> /bin/java /opt/app.jar /lib/libc </pre> <pre data-bbox="1388 732 1549 857"> {   "manifests": {     "platform": {       "os": "linux",       ...     }   } } </pre> <pre data-bbox="1688 695 1843 906"> {   ...   "config": {     "Cmd": [       "java", "-jar",       "app.jar"     ],     ...   } } </pre> <p data-bbox="632 1036 1478 1105"><a href="https://github.com/opencontainers/image-spec/blob/a6af2b480dcfc001ba975f44de53001c873cb0ef/spec.md">https://github.com/opencontainers/image-spec/blob/a6af2b480dcfc001ba975f44de53001c873cb0ef/spec.md</a></p> </div>

Claim 1	Accused Instrumentalities
	<h2 data-bbox="653 245 1297 305">OCI Image Configuration</h2> <p data-bbox="653 358 1913 521">An OCI <i>Image</i> is an ordered collection of root filesystem changes and the corresponding execution parameters for use within a container runtime. This specification outlines the JSON format describing images for use with a container runtime and execution tool and its relationship to filesystem changesets, described in <a href="#">Layers</a>.</p> <p data-bbox="653 558 1661 591">This section defines the <code>application/vnd.oci.image.config.v1+json</code> <a href="#">media type</a>.</p> <p data-bbox="632 623 1503 695"><a href="https://github.com/opencontainers/image-spec/blob/a6af2b480dcfc001ba975f44de53001c873cb0ef/config.md">https://github.com/opencontainers/image-spec/blob/a6af2b480dcfc001ba975f44de53001c873cb0ef/config.md</a></p>


Claim 1	Accused Instrumentalities
	<p data-bbox="661 251 745 284"><b>Layer</b></p> <ul data-bbox="688 324 1919 673" style="list-style-type: none"> <li>• Image filesystems are composed of <i>layers</i>.</li> <li>• Each layer represents a set of filesystem changes in a tar-based <a href="#">layer format</a>, recording files to be added, changed, or deleted relative to its parent layer.</li> <li>• Layers do not have configuration metadata such as environment variables or default arguments - these are properties of the image as a whole rather than any particular layer.</li> <li>• Using a layer-based or union filesystem such as AUFS, or by computing the diff from filesystem snapshots, the filesystem changeset can be used to present a series of image layers as if they were one cohesive filesystem.</li> </ul> <p data-bbox="661 722 856 755"><b>Image JSON</b></p> <ul data-bbox="688 795 1919 1144" style="list-style-type: none"> <li>• Each image has an associated JSON structure which describes some basic information about the image such as date created, author, as well as execution/runtime configuration like its entrypoint, default arguments, networking, and volumes.</li> <li>• The JSON structure also references a cryptographic hash of each layer used by the image, and provides history information for those layers.</li> <li>• This JSON is considered to be immutable, because changing it would change the computed <a href="#">ImageID</a>.</li> <li>• Changing it means creating a new derived image, instead of changing the existing image.</li> </ul> <p data-bbox="634 1169 1503 1242"><a href="https://github.com/opencontainers/image-spec/blob/a6af2b480dcfc001ba975f44de53001c873cb0ef/config.md">https://github.com/opencontainers/image-spec/blob/a6af2b480dcfc001ba975f44de53001c873cb0ef/config.md</a></p>


Claim 1	Accused Instrumentalities
	<ul style="list-style-type: none"> <li>• <b>rootfs object</b>, REQUIRED  The rootfs key references the layer content addresses used by the image. This makes the image config hash depend on the filesystem hash.</li> <li>◦ <b>type string</b>, REQUIRED  MUST be set to <code>layers</code>. Implementations MUST generate an error if they encounter a unknown value while verifying or unpacking an image.</li> <li>◦ <b>diff_ids array of strings</b>, REQUIRED  An array of layer content hashes ( <code>DiffIDs</code> ), in order from first to last.  <a href="https://github.com/opencontainers/image-spec/blob/a6af2b480dcfc001ba975f44de53001c873cb0ef/config.md">https://github.com/opencontainers/image-spec/blob/a6af2b480dcfc001ba975f44de53001c873cb0ef/config.md</a></li> </ul>
[1b] wherein the set of associated system files are compatible with a local kernel of at least some of the plurality of different operating systems,	<p>In the method practiced by Google through the Accused Instrumentalities, the set of associated system files are compatible with a local kernel of at least some of the plurality of different operating systems.</p> <p>The system files in the container are compatible with the host kernel, for example because they are linked against the Linux kernel and the supported host operating systems also use the Linux kernel, which has a stable binary interface.</p> <p>See discussion and evidence in element [1a] above.</p> <p>See also, e.g.:</p>



Claim 1	Accused Instrumentalities
	<p>A container is a way of packaging a given application's code and dependencies so that the application will run easily in any computing environment. This solves the common problem of</p> <p>The container image specifies the container's file system. For example, if you're running a Node.js application, the container image would contain your app, Node.js, and other dependencies like Linux system libraries (except the kernel). A container image usually extends a base operating system image, or <b>base image</b>. This base image is the basis of your container, so you'll want to ensure that it's properly patched and free from known vulnerabilities.</p> <p>Containers use specific features of the Linux kernel that "trick" individual applications into thinking they're in their own unique environment, even though multiple applications share the same host kernel. (If you're not familiar with the Linux kernel, it's a part of the operating system that communicates between processes--requests that do user tasks like opening a file, running a program-- and the hardware. It manages resources like memory and CPU to meet these requests).</p> <p><a href="https://services.google.com/fh/files/misc/why_container_security_matters.pdf">https://services.google.com/fh/files/misc/why_container_security_matters.pdf</a></p>

Claim 1	Accused Instrumentalities
	<p>Containers can run virtually anywhere, greatly easing development and deployment: on Linux, Windows, and Mac operating systems; on virtual machines or on physical servers; on a developer's machine or in data centers on-premises; and of course, in the public cloud.</p> <p><a href="https://cloud.google.com/learn/what-are-containers">https://cloud.google.com/learn/what-are-containers</a></p>
<p>[1c] the containers of application software excluding a kernel,</p>	<p>In the method practiced by Google and/or its customer through the Accused Instrumentalities, the containers of application software exclude a kernel.</p> <p><i>See</i> discussion and evidence in element [1a] above.</p> <p><i>See also, e.g.:</i></p> <ul style="list-style-type: none"> <li>• <b>Higher utilization and density</b>, leveraging automatic bin-packing and auto-scaling capabilities, Kubernetes places containers optimally in nodes based on required resources while scaling as needed, without impairing availability. In addition, unlike VMs, all containers on a single node share one copy of the operating system and don't each require their own OS image and vCPU, resulting in a much smaller memory footprint and CPU needs. This means more workloads running on fewer compute resources.</li> </ul> <p><a href="https://cloud.google.com/blog/products/containers-kubernetes/how-migrate-for-anthos-improves-vm-to-container-migration">https://cloud.google.com/blog/products/containers-kubernetes/how-migrate-for-anthos-improves-vm-to-container-migration</a></p>

Claim 1	Accused Instrumentalities
	<p>workloads onto each server. As such, the architecture of containers means that they're deployed with multiple containers sharing the same kernel.</p>  <p>The diagram illustrates a virtual machine environment. At the top, there are two colored boxes: an orange box labeled 'Container A' and a green box labeled 'Container B'. Below these boxes is a blue box labeled 'host kernel'. A red dashed line with arrows at both ends connects the bottom of 'Container A' to the 'host kernel' box. Below the 'host kernel' box is a light gray box labeled 'virtual machine'. The entire diagram is enclosed in a light gray border.</p> <p><a href="https://services.google.com/fh/files/misc/why_container_security_matters.pdf">https://services.google.com/fh/files/misc/why_container_security_matters.pdf</a></p> <p>6. Do Docker containers package up the entire OS and make it easier to deploy?</p> <p>Docker containers do not package up the OS. They package up the applications with everything that the application needs to run. The engine is installed on top of the OS running on a host. Containers share the OS kernel allowing a single host to run multiple containers.</p> <p><a href="https://www.docker.com/blog/the-10-most-common-questions-it-admins-ask-about-docker/">https://www.docker.com/blog/the-10-most-common-questions-it-admins-ask-about-docker/</a></p>
<p>[1d] wherein some or all of the associated system files within a container stored in memory are utilized in place of the associated local system files that remain resident on the server,</p>	<p>In the method practiced by Google and/or its customer through the Accused Instrumentalities, some or all of the associated system files within a container stored in memory are utilized in place of the associated local system files that remain resident on the server.</p> <p>For example, each container will utilize its own local system files, including libraries such as libc/glibc and configuration files, not the corresponding libraries and configuration files of the host OS.</p> <p>See discussion and evidence in element [1a] above.</p> <p>See also, e.g.:</p>

Claim 1	Accused Instrumentalities
	<p>One of the primary reasons to adopt containers is for your applications to be decoupled from the underlying environment and support higher resource utilization by “bin packing” multiple workloads onto each server. As such, the architecture of containers means that they’re deployed with multiple containers sharing the same kernel.</p> <p>The container image specifies the container’s file system. For example, if you’re running a Node.js application, the container image would contain your app, Node.js, and other dependencies like Linux system libraries (except the kernel). A container image usually extends a base operating system image, or <b>base image</b>. This base image is the basis of your container, so you’ll want to ensure that it’s properly patched and free from known vulnerabilities.</p> <p><a href="https://services.google.com/fh/files/misc/why_container_security_matters.pdf">https://services.google.com/fh/files/misc/why_container_security_matters.pdf</a></p>  <p>The diagram illustrates the architectural differences between a traditional source machine and a Google containers platform. On the left, the 'Source Machine' shows a stack where applications (App 1, App 2, App 3) and services (Logging, Tomcat server) are directly layered on top of the 'OS Kernel + drivers' and 'File system'. On the right, the 'Google containers platform' shows a 'Flexible deployment' layer containing a 'Container image' (with App 2, Tomcat, and Services) which sits on a 'Persistent volume'. This entire container stack is managed by a layer including 'Networking', 'Logging', and 'OS Kernel + drivers'. Two blue arrows indicate the migration of 'App 2' and its associated 'Services' from the source machine to the container image in the Google platform.</p> <p><a href="https://cloud.google.com/blog/products/application-modernization/shift-your-apps-to-container-based-workloads-on-the-command-line">https://cloud.google.com/blog/products/application-modernization/shift-your-apps-to-container-based-workloads-on-the-command-line</a></p>

Claim 1	Accused Instrumentalities
<p>[1e] wherein said associated system files utilized in place of the associated local system files are copies or modified copies of the associated local system files that remain resident on the server,</p>	<p>In the method practiced by Google and/or its customer through the Accused Instrumentalities, said associated system files utilized in place of the associated local system files are copies or modified copies of the associated local system files that remain resident on the server.</p> <p>For example, in some cases the host OS and container will use one or more identical system files, for example when both the host and the container incorporate the same Linux distribution version, or when both host and container use the same version of libc. In other cases modified copies are used instead, for example when different versions of the same library, or configuration files with different parameters, are used by the host and container.</p> <p><i>See</i> discussion and evidence in element [1a] above.</p> <p><i>See also, e.g.:</i></p> <p>One of the primary reasons to adopt containers is for your applications to be decoupled from the underlying environment and support higher resource utilization by “bin packing” multiple workloads onto each server. As such, the architecture of containers means that they’re deployed with multiple containers sharing the same kernel.</p> <p>The container image specifies the container’s file system. For example, if you’re running a Node.js application, the container image would contain your app, Node.js, and other dependencies like Linux system libraries (except the kernel). A container image usually extends a base operating system image, or <b>base image</b>. This base image is the basis of your container, so you’ll want to ensure that it’s properly patched and free from known vulnerabilities.</p> <p><a href="https://services.google.com/fh/files/misc/why_container_security_matters.pdf">https://services.google.com/fh/files/misc/why_container_security_matters.pdf</a></p>

Claim 1	Accused Instrumentalities
	<p data-bbox="640 235 1486 354">COPY and ADD : These commands copy files and directories from your local filesystem into the Docker image. They are often used to include your application code, configuration files, and dependencies.</p> <p data-bbox="640 365 1919 435"><a href="https://medium.com/@swalperen3008/what-is-dockerize-and-dockerize-your-project-a-step-by-step-guide-899c48a34df6">https://medium.com/@swalperen3008/what-is-dockerize-and-dockerize-your-project-a-step-by-step-guide-899c48a34df6</a></p> <h2 data-bbox="667 467 978 516">Container images</h2> <p data-bbox="667 544 1264 673">A <a href="#">container image</a> is a ready-to-run software package containing everything needed to run an application: the code and any runtime it requires, application and system libraries, and default values for any essential settings.</p> <p data-bbox="640 695 1228 727"><a href="https://kubernetes.io/docs/concepts/containers/">https://kubernetes.io/docs/concepts/containers/</a></p>

Claim 1	Accused Instrumentalities
	<h2 data-bbox="646 248 1272 316">About storage drivers</h2> <p data-bbox="646 363 1871 488">To use storage drivers effectively, it's important to know how Docker builds and stores images, and how these images are used by containers. You can use this information to make informed choices about the best way to persist data from your applications and avoid performance problems along the way.</p> <h2 data-bbox="646 557 1564 613">Storage drivers versus Docker volumes</h2> <p data-bbox="646 651 1913 919">Docker uses storage drivers to store image layers, and to store data in the writable layer of a container. The container's writable layer doesn't persist after the container is deleted, but is suitable for storing ephemeral data that is generated at runtime. Storage drivers are optimized for space efficiency, but (depending on the storage driver) write speeds are lower than native file system performance, especially for storage drivers that use a copy-on-write filesystem. Write-intensive applications, such as database storage, are impacted by a performance overhead, particularly if pre-existing data exists in the read-only layer.</p> <p data-bbox="646 967 1902 1092">Use Docker volumes for write-intensive data, data that must persist beyond the container's lifespan, and data that must be shared between containers. Refer to the <a data-bbox="1339 1016 1535 1044" href="#">volumes section</a> to learn how to use volumes to persist data and improve performance.</p> <p data-bbox="636 1122 1226 1157"><a data-bbox="636 1122 1226 1157" href="https://docs.docker.com/storage/storagedriver/">https://docs.docker.com/storage/storagedriver/</a></p>

Claim 1	Accused Instrumentalities
	<h2 data-bbox="657 245 1081 302">Images and layers</h2> <p data-bbox="657 337 1822 415">A Docker image is built up from a series of layers. Each layer represents an instruction in the image's Dockerfile. Each layer except the very last one is read-only. Consider the following Dockerfile:</p> <pre data-bbox="674 483 1453 797"> # syntax=docker/dockerfile:1  FROM ubuntu:22.04 LABEL org.opencontainers.image.authors="org@example.com" COPY . /app RUN make /app RUN rm -r \$HOME/.cache CMD python /app/app.py </pre> <p data-bbox="657 862 1900 1170">This Dockerfile contains four commands. Commands that modify the filesystem create a layer. The <code>FROM</code> statement starts out by creating a layer from the <code>ubuntu:22.04</code> image. The <code>LABEL</code> command only modifies the image's metadata, and doesn't produce a new layer. The <code>COPY</code> command adds some files from your Docker client's current directory. The first <code>RUN</code> command builds your application using the <code>make</code> command, and writes the result to a new layer. The second <code>RUN</code> command removes a cache directory, and writes the result to a new layer. Finally, the <code>CMD</code> instruction specifies what command to run within the container, which only modifies the image's metadata, which doesn't produce an image layer.</p> <p data-bbox="634 1192 1226 1224"><a href="https://docs.docker.com/storage/storagedriver/">https://docs.docker.com/storage/storagedriver/</a></p>



Claim 1	Accused Instrumentalities
	<p>Each layer is only a set of differences from the layer before it. Note that both <i>adding</i>, and <i>removing</i> files will result in a new layer. In the example above, the <code>\$HOME/.cache</code> directory is removed, but will still be available in the previous layer and add up to the image's total size. Refer to the <a href="#">Best practices for writing Dockerfiles</a> and <a href="#">use multi-stage builds</a> sections to learn how to optimize your Dockerfiles for efficient images.</p> <p>The layers are stacked on top of each other. When you create a new container, you add a new writable layer on top of the underlying layers. This layer is often called the "container layer". All changes made to the running container, such as writing new files, modifying existing files, and deleting files, are written to this thin writable container layer. The diagram below shows a container based on an <code>ubuntu:15.04</code> image.</p> <div data-bbox="898 724 1633 1300" data-label="Diagram"> </div> <p><a href="https://docs.docker.com/storage/storagedriver/">https://docs.docker.com/storage/storagedriver/</a></p>

Claim 1	Accused Instrumentalities
<p>[1f] and wherein the application software cannot be shared between the plurality of secure containers of application software,</p>	<p>In the method practiced by Google through the Accused Instrumentalities, the application software cannot be shared between the plurality of secure containers of application software.</p> <p>For example, each container has an isolated runtime environment that cannot be accessed by other containers, for example including a per-container writeable layer or other ephemeral per-container storage. For another example, when the plurality of secure containers each corresponds to a different container image, each container cannot access another container's image and therefore application software.</p> <p><i>See, e.g.:</i></p> <p>Containers use specific features of the Linux kernel that “trick” individual applications into thinking they're in their own unique environment, even though multiple applications share the same host kernel. (If you're not familiar with the Linux kernel, it's a part of the operating system that communicates between processes--requests that do user tasks like opening a file, running a program-- and the hardware. It manages resources like memory and CPU to meet these requests).</p> <p><a href="https://services.google.com/fh/files/misc/why_container_security_matters.pdf">https://services.google.com/fh/files/misc/why_container_security_matters.pdf</a></p> <p>The core components of the Linux kernel that are used for containers are <b>cgroups</b> — control groups, which define the resources like CPU and memory which are available to a given process — and <b>namespaces</b>, which are a way of separating processes by restricting what each process can see, so that system resources “appear” isolated to the process.</p> <p><a href="https://services.google.com/fh/files/misc/why_container_security_matters.pdf">https://services.google.com/fh/files/misc/why_container_security_matters.pdf</a></p> <p>reason. Furthermore, files within a container are inaccessible to other containers running in the same Pod <a href="#">🔗</a>. The <a href="#">Kubernetes</a></p> <p><a href="https://cloud.google.com/kubernetes-engine/docs/concepts/volumes">https://cloud.google.com/kubernetes-engine/docs/concepts/volumes</a></p>

Claim 1	Accused Instrumentalities
	<p>A <i>Pod</i> (as in a pod of whales or pea pod) is a group of one or more <u>containers</u>, with shared storage and network resources, and a specification for how to run the containers. A Pod's contents are always co-located and co-scheduled, and run in a shared context. A Pod models an application-specific "logical host": it contains one or more application containers which are relatively tightly coupled. In non-cloud contexts, applications executed on the same physical or virtual machine are analogous to cloud applications executed on the same logical host.</p> <p>The shared context of a Pod is a set of Linux namespaces, cgroups, and potentially other facets of isolation - the same things that isolate a <u>container</u>. Within a Pod's context, the individual applications may have further sub-isolations applied.</p> <p><a href="https://kubernetes.io/docs/concepts/workloads/pods/">https://kubernetes.io/docs/concepts/workloads/pods/</a></p> <p>ranges can access. <a href="#">GKE Sandbox</a> for the Standard mode of operation provides a second layer of defense between containerized workloads on GKE for <a href="#">enhanced workload security</a>. GKE <a href="https://cloud.google.com/kubernetes-engine#section-2">https://cloud.google.com/kubernetes-engine#section-2</a></p>

Claim 1	Accused Instrumentalities
	<h2 data-bbox="646 248 1272 316">About storage drivers</h2> <p data-bbox="646 362 1871 488">To use storage drivers effectively, it's important to know how Docker builds and stores images, and how these images are used by containers. You can use this information to make informed choices about the best way to persist data from your applications and avoid performance problems along the way.</p> <h2 data-bbox="646 557 1564 613">Storage drivers versus Docker volumes</h2> <p data-bbox="646 651 1913 919">Docker uses storage drivers to store image layers, and to store data in the writable layer of a container. The container's writable layer doesn't persist after the container is deleted, but is suitable for storing ephemeral data that is generated at runtime. Storage drivers are optimized for space efficiency, but (depending on the storage driver) write speeds are lower than native file system performance, especially for storage drivers that use a copy-on-write filesystem. Write-intensive applications, such as database storage, are impacted by a performance overhead, particularly if pre-existing data exists in the read-only layer.</p> <p data-bbox="646 967 1902 1094">Use Docker volumes for write-intensive data, data that must persist beyond the container's lifespan, and data that must be shared between containers. Refer to the <a data-bbox="1339 1016 1535 1040" href="#">volumes section</a> to learn how to use volumes to persist data and improve performance.</p> <p data-bbox="636 1122 1224 1154"><a data-bbox="636 1122 1224 1154" href="https://docs.docker.com/storage/storagedriver/">https://docs.docker.com/storage/storagedriver/</a></p>

Claim 1	Accused Instrumentalities
	<h2 data-bbox="657 245 1081 302">Images and layers</h2> <p data-bbox="657 337 1822 415">A Docker image is built up from a series of layers. Each layer represents an instruction in the image's Dockerfile. Each layer except the very last one is read-only. Consider the following Dockerfile:</p> <pre data-bbox="674 483 1453 797"> # syntax=docker/dockerfile:1  FROM ubuntu:22.04 LABEL org.opencontainers.image.authors="org@example.com" COPY . /app RUN make /app RUN rm -r \$HOME/.cache CMD python /app/app.py </pre> <p data-bbox="657 862 1900 1170">This Dockerfile contains four commands. Commands that modify the filesystem create a layer. The <code>FROM</code> statement starts out by creating a layer from the <code>ubuntu:22.04</code> image. The <code>LABEL</code> command only modifies the image's metadata, and doesn't produce a new layer. The <code>COPY</code> command adds some files from your Docker client's current directory. The first <code>RUN</code> command builds your application using the <code>make</code> command, and writes the result to a new layer. The second <code>RUN</code> command removes a cache directory, and writes the result to a new layer. Finally, the <code>CMD</code> instruction specifies what command to run within the container, which only modifies the image's metadata, which doesn't produce an image layer.</p> <p data-bbox="634 1192 1226 1224"><a href="https://docs.docker.com/storage/storagedriver/">https://docs.docker.com/storage/storagedriver/</a></p>

Claim 1	Accused Instrumentalities
	<p>Each layer is only a set of differences from the layer before it. Note that both <i>adding</i>, and <i>removing</i> files will result in a new layer. In the example above, the <code>\$HOME/.cache</code> directory is removed, but will still be available in the previous layer and add up to the image's total size. Refer to the <a href="#">Best practices for writing Dockerfiles</a> and <a href="#">use multi-stage builds</a> sections to learn how to optimize your Dockerfiles for efficient images.</p> <p>The layers are stacked on top of each other. When you create a new container, you add a new writable layer on top of the underlying layers. This layer is often called the "container layer". All changes made to the running container, such as writing new files, modifying existing files, and deleting files, are written to this thin writable container layer. The diagram below shows a container based on an <code>ubuntu:15.04</code> image.</p> <div data-bbox="898 724 1633 1300" data-label="Diagram"> <p>The diagram shows a stack of four blue boxes representing 'Image Layers (R/O)' (Read-Only). From bottom to top, the layers are: 'd3a1f33e8a5a' (188.1 MB), 'c22013c84729' (194.5 KB), 'd74508fb6632' (1.895 KB), and '91e54dfb1179' (0 B). The stack is labeled 'ubuntu:15.04'. Above the stack is a dashed box labeled 'Thin R/W layer' (Container layer). Arrows indicate bidirectional communication between the container layer and the image layers. A padlock icon is shown next to the image layers stack, indicating they are read-only.</p> <p>Container (based on ubuntu:15.04 image)</p> <p><a href="https://docs.docker.com/storage/storagedriver/">https://docs.docker.com/storage/storagedriver/</a></p> </div>


Claim 1	Accused Instrumentalities
<p>[1g] and wherein each of the containers has a unique root file system that is different from an operating system's root file system.</p>	<p>In the method practiced by Google through the Accused Instrumentalities, each of the containers has a unique root file system that is different from an operating system's root file system.</p> <p>For example, the container's root file system comprises the image layer(s), an ephemeral writeable layer (e.g., in Docker terminology the container layer), and optionally one or more volumes. This root file system is distinct and isolated from the host operating system's root file system.</p> <p><i>See, e.g.:</i></p> <p>The original purpose of the cgroup, <b>chroot</b>, and namespace facilities in the kernel was to protect applications from noisy, nosey, and messy neighbors. Combining these with container images created an abstraction that also isolates applications from the (heterogeneous) operating systems on which they run. This decoupling of image and OS makes it possible to provide the same deployment environment in both development and production, which, in turn, improves deployment reliability and speeds up development by reducing inconsistencies and friction.</p> <p>“Borg, Omega, and, Kubernetes,”  <a href="https://static.googleusercontent.com/media/research.google.com/en//pubs/archive/44843.pdf">https://static.googleusercontent.com/media/research.google.com/en//pubs/archive/44843.pdf</a></p> <p>In Docker and Kubernetes, the container's root filesystem (rootfs) is based on the filesystem packaged with the image. The image's filesystem is immutable. Any change a container makes to the rootfs is stored separately and is destroyed with the container. This way, the image's filesystem  <a href="https://opensource.googleblog.com/2023/04/gvisor-improves-performance-with-root-filesystem-overlay.html">https://opensource.googleblog.com/2023/04/gvisor-improves-performance-with-root-filesystem-overlay.html</a></p>

Claim 1	Accused Instrumentalities
	<p>To use a volume, specify the volumes to provide for the Pod in <code>.spec.volumes</code> and declare where to mount those volumes into containers in <code>.spec.containers[*].volumeMounts</code>. A process in a container sees a filesystem view composed from the initial contents of the container image, plus volumes (if defined) mounted inside the container. The process sees a root filesystem that initially matches the contents of the container image. Any writes to within that filesystem hierarchy, if allowed, affect what that process views when it performs a subsequent filesystem access. Volumes mount at the <a href="#">specified paths</a> within the image. For each container defined within a Pod, you must independently specify where to mount each volume that the container uses.</p> <p><a href="https://kubernetes.io/docs/concepts/storage/volumes/">https://kubernetes.io/docs/concepts/storage/volumes/</a></p>



Claim 1	Accused Instrumentalities
	<h2 data-bbox="646 248 1272 316">About storage drivers</h2> <p data-bbox="646 362 1871 488">To use storage drivers effectively, it's important to know how Docker builds and stores images, and how these images are used by containers. You can use this information to make informed choices about the best way to persist data from your applications and avoid performance problems along the way.</p> <h2 data-bbox="646 557 1564 613">Storage drivers versus Docker volumes</h2> <p data-bbox="646 651 1913 919">Docker uses storage drivers to store image layers, and to store data in the writable layer of a container. The container's writable layer doesn't persist after the container is deleted, but is suitable for storing ephemeral data that is generated at runtime. Storage drivers are optimized for space efficiency, but (depending on the storage driver) write speeds are lower than native file system performance, especially for storage drivers that use a copy-on-write filesystem. Write-intensive applications, such as database storage, are impacted by a performance overhead, particularly if pre-existing data exists in the read-only layer.</p> <p data-bbox="646 967 1902 1094">Use Docker volumes for write-intensive data, data that must persist beyond the container's lifespan, and data that must be shared between containers. Refer to the <a data-bbox="1339 1016 1535 1040" href="#">volumes section</a> to learn how to use volumes to persist data and improve performance.</p> <p data-bbox="636 1122 1226 1154"><a data-bbox="636 1122 1226 1154" href="https://docs.docker.com/storage/storagedriver/">https://docs.docker.com/storage/storagedriver/</a></p>

Claim 1	Accused Instrumentalities
	<h2 data-bbox="657 245 1081 302">Images and layers</h2> <p data-bbox="657 337 1822 415">A Docker image is built up from a series of layers. Each layer represents an instruction in the image's Dockerfile. Each layer except the very last one is read-only. Consider the following Dockerfile:</p> <pre data-bbox="674 483 1453 797"> # syntax=docker/dockerfile:1  FROM ubuntu:22.04 LABEL org.opencontainers.image.authors="org@example.com" COPY . /app RUN make /app RUN rm -r \$HOME/.cache CMD python /app/app.py </pre> <p data-bbox="657 862 1900 1170">This Dockerfile contains four commands. Commands that modify the filesystem create a layer. The <code>FROM</code> statement starts out by creating a layer from the <code>ubuntu:22.04</code> image. The <code>LABEL</code> command only modifies the image's metadata, and doesn't produce a new layer. The <code>COPY</code> command adds some files from your Docker client's current directory. The first <code>RUN</code> command builds your application using the <code>make</code> command, and writes the result to a new layer. The second <code>RUN</code> command removes a cache directory, and writes the result to a new layer. Finally, the <code>CMD</code> instruction specifies what command to run within the container, which only modifies the image's metadata, which doesn't produce an image layer.</p> <p data-bbox="634 1192 1226 1224"><a href="https://docs.docker.com/storage/storagedriver/">https://docs.docker.com/storage/storagedriver/</a></p>

Claim 1	Accused Instrumentalities
	<p>Each layer is only a set of differences from the layer before it. Note that both <i>adding</i>, and <i>removing</i> files will result in a new layer. In the example above, the <code>\$HOME/.cache</code> directory is removed, but will still be available in the previous layer and add up to the image's total size. Refer to the <a href="#">Best practices for writing Dockerfiles</a> and <a href="#">use multi-stage builds</a> sections to learn how to optimize your Dockerfiles for efficient images.</p> <p>The layers are stacked on top of each other. When you create a new container, you add a new writable layer on top of the underlying layers. This layer is often called the "container layer". All changes made to the running container, such as writing new files, modifying existing files, and deleting files, are written to this thin writable container layer. The diagram below shows a container based on an <code>ubuntu:15.04</code> image.</p>  <p>The diagram illustrates the layer architecture of a Docker container. It shows a stack of four image layers, each represented by a blue rectangle with a unique hash and a size:     <ul style="list-style-type: none"> <li>Top layer: 91e54dfb1179, 0 B</li> <li>Second layer: d74508fb6632, 1.895 KB</li> <li>Third layer: c22013c84729, 194.5 KB</li> <li>Bottom layer: d3a1f33e8a5a, 188.1 MB</li> </ul>     These layers are collectively labeled as 'Image Layers (R/O)' (Read-Only) on the right. A padlock icon is shown next to this label. Above this stack is a dashed box labeled 'Thin R/W layer' (Read-Write), which is identified as the 'Container layer' by an arrow. Bidirectional arrows connect the container layer to the top image layer. Below the stack, the text 'ubuntu:15.04' and 'Container (based on ubuntu:15.04 image)' are shown.   </p> <p><a href="https://docs.docker.com/storage/storagedriver/">https://docs.docker.com/storage/storagedriver/</a></p>

Claim 1	Accused Instrumentalities
	<p>The original purpose of the cgroup, <b>chroot</b>, and namespace facilities in the kernel was to protect applications from noisy, nosey, and messy neighbors. Combining these with container images created an abstraction that also isolates applications from the [heterogeneous] operating systems</p> <p><a href="https://kubernetes.io/docs/concepts/storage/volumes/">https://kubernetes.io/docs/concepts/storage/volumes/</a></p> <h2>Container environment</h2> <p>The Kubernetes Container environment provides several important resources to Containers:</p> <ul style="list-style-type: none"><li>• A filesystem, which is a combination of an <a href="#">image</a> and one or more <a href="#">volumes</a>.</li><li>• Information about the Container itself.</li><li>• Information about other objects in the cluster.</li></ul> <p><a href="https://kubernetes.io/docs/concepts/containers/container-environment/">https://kubernetes.io/docs/concepts/containers/container-environment/</a></p>

Claim 1	Accused Instrumentalities
	<h2 data-bbox="659 250 877 315">Images</h2> <p data-bbox="659 347 1520 500">A container image represents binary data that encapsulates an application and all its software dependencies. Container images are executable software bundles that can run standalone and that make very well defined assumptions about their runtime environment.</p> <p data-bbox="659 537 1528 609">You typically create a container image of your application and push it to a registry before referring to it in a <u>Pod</u>.</p> <p data-bbox="634 636 1329 669"><a href="https://kubernetes.io/docs/concepts/containers/images/">https://kubernetes.io/docs/concepts/containers/images/</a></p> <h2 data-bbox="653 711 919 769">Volumes</h2> <p data-bbox="653 808 1482 880">On-disk files in a container are ephemeral, which presents some problems for non-trivial applications when running in containers.</p> <p data-bbox="653 889 1430 922">One problem occurs when a container crashes or is stopped.</p> <p data-bbox="653 932 1528 1253">Container state is not saved so all of the files that were created or modified during the lifetime of the container are lost. During a crash, kubelet restarts the container with a clean state. Another problem occurs when multiple containers are running in a <u>Pod</u> and need to share files. It can be challenging to setup and access a shared filesystem across all of the containers. The Kubernetes <u>volume</u> abstraction solves both of these problems. Familiarity with <u>Pods</u> is suggested.</p> <p data-bbox="634 1279 1308 1312"><a href="https://kubernetes.io/docs/concepts/storage/volumes/">https://kubernetes.io/docs/concepts/storage/volumes/</a></p>

Claim 1	Accused Instrumentalities
	<div data-bbox="659 253 1299 315"><h2>Open Container Initiative</h2><hr/></div> <div data-bbox="659 375 1186 423"><h3>Image Format Specification</h3><hr/></div> <div data-bbox="659 469 1904 547"><p>This specification defines an OCI Image, consisting of an <a href="#">image manifest</a>, an <a href="#">image index</a> (optional), a set of <a href="#">filesystem layers</a>, and a <a href="#">configuration</a>.</p></div> <div data-bbox="659 578 1908 656"><p>The goal of this specification is to enable the creation of interoperable tools for building, transporting, and preparing a container image to run.</p></div> <div data-bbox="625 680 1482 753"><p><a href="https://github.com/opencontainers/image-spec/blob/a6af2b480dcfc001ba975f44de53001c873cb0ef/spec.md">https://github.com/opencontainers/image-spec/blob/a6af2b480dcfc001ba975f44de53001c873cb0ef/spec.md</a></p></div>

Claim 1	Accused Instrumentalities
	<p data-bbox="648 250 831 289"><b>Overview</b></p> <p data-bbox="648 345 1892 586">At a high level the image manifest contains metadata about the contents and dependencies of the image including the content-addressable identity of one or more <a href="#">filesystem layer changeset</a> archives that will be unpacked to make up the final runnable filesystem. The image configuration includes information such as application arguments, environments, etc. The image index is a higher-level manifest which points to a list of manifests and descriptors. Typically, these manifests may provide different implementations of the image, possibly varying by platform or other attributes.</p> <div data-bbox="667 626 1906 1008"> <p>The diagram illustrates the components of an OCI image. On the left, a code block shows a Java class: <code>public class HelloWorld { public static void main(String[] args) { System.out.println("Hello, World"); } }</code>. An arrow points from this code to a cylinder labeled 'layer' containing the paths <code>/bin/java</code>, <code>/opt/app.jar</code>, and <code>/lib/libc</code>. To the right of the layer is a plus sign, followed by a document icon labeled 'image index' containing a JSON snippet: <code>{ "manifests": { "platform": { "os": "linux", ... } ... }</code>. Another plus sign follows, leading to a document icon labeled 'config' containing a JSON snippet: <code>{ ... "config": { "Cmd": [ "java", "-jar", "app.jar" ], ... }</code>. Each of the three components (layer, image index, and config) has a small square icon with the letters 'Ci' in the top-left corner.</p> </div> <p data-bbox="632 1036 1478 1105"><a href="https://github.com/opencontainers/image-spec/blob/a6af2b480dcfc001ba975f44de53001c873cb0ef/spec.md">https://github.com/opencontainers/image-spec/blob/a6af2b480dcfc001ba975f44de53001c873cb0ef/spec.md</a></p>

Claim 1	Accused Instrumentalities
	<h2 data-bbox="653 245 1297 305">OCI Image Configuration</h2> <p data-bbox="653 358 1913 521">An OCI <i>Image</i> is an ordered collection of root filesystem changes and the corresponding execution parameters for use within a container runtime. This specification outlines the JSON format describing images for use with a container runtime and execution tool and its relationship to filesystem changesets, described in <a href="#">Layers</a>.</p> <p data-bbox="653 558 1661 591">This section defines the <code>application/vnd.oci.image.config.v1+json</code> <a href="#">media type</a>.</p> <p data-bbox="632 623 1503 695"><a href="https://github.com/opencontainers/image-spec/blob/a6af2b480dcfc001ba975f44de53001c873cb0ef/config.md">https://github.com/opencontainers/image-spec/blob/a6af2b480dcfc001ba975f44de53001c873cb0ef/config.md</a></p>




Claim 1	Accused Instrumentalities
	<p data-bbox="661 253 747 289">Layer</p> <ul data-bbox="688 329 1919 672" style="list-style-type: none"> <li>• Image filesystems are composed of <i>layers</i>.</li> <li>• Each layer represents a set of filesystem changes in a tar-based <a href="#">layer format</a>, recording files to be added, changed, or deleted relative to its parent layer.</li> <li>• Layers do not have configuration metadata such as environment variables or default arguments - these are properties of the image as a whole rather than any particular layer.</li> <li>• Using a layer-based or union filesystem such as AUFS, or by computing the diff from filesystem snapshots, the filesystem changeset can be used to present a series of image layers as if they were one cohesive filesystem.</li> </ul> <p data-bbox="661 724 856 760">Image JSON</p> <ul data-bbox="688 800 1919 1143" style="list-style-type: none"> <li>• Each image has an associated JSON structure which describes some basic information about the image such as date created, author, as well as execution/runtime configuration like its entrypoint, default arguments, networking, and volumes.</li> <li>• The JSON structure also references a cryptographic hash of each layer used by the image, and provides history information for those layers.</li> <li>• This JSON is considered to be immutable, because changing it would change the computed <a href="#">ImageID</a>.</li> <li>• Changing it means creating a new derived image, instead of changing the existing image.</li> </ul> <p data-bbox="634 1174 1503 1240"><a href="https://github.com/opencontainers/image-spec/blob/a6af2b480dcfc001ba975f44de53001c873cb0ef/config.md">https://github.com/opencontainers/image-spec/blob/a6af2b480dcfc001ba975f44de53001c873cb0ef/config.md</a></p>

Claim 1	Accused Instrumentalities
	<ul style="list-style-type: none"> <li>• <b>rootfs object</b>, REQUIRED</li> </ul> <p>The rootfs key references the layer content addresses used by the image. This makes the image config hash depend on the filesystem hash.</p> <ul style="list-style-type: none"> <li>◦ <b>type string</b>, REQUIRED</li> </ul> <p>MUST be set to <code>layers</code>. Implementations MUST generate an error if they encounter a unknown value while verifying or unpacking an image.</p> <ul style="list-style-type: none"> <li>◦ <b>diff_ids array of strings</b>, REQUIRED</li> </ul> <p>An array of layer content hashes ( <code>DiffIDs</code> ), in order from first to last.</p> <p><a href="https://github.com/opencontainers/image-spec/blob/a6af2b480dcfc001ba975f44de53001c873cb0ef/config.md">https://github.com/opencontainers/image-spec/blob/a6af2b480dcfc001ba975f44de53001c873cb0ef/config.md</a></p>

**Claim 2**

Claim 2	Accused Instrumentalities
<p>2. A method as defined in claim 1, wherein each container has an execution file associated therewith for starting the one or more applications.</p>	<p>Google and/or its customer practices, through the Accused Instrumentalities, a method as defined in claim 1, wherein each container has an execution file associated therewith for starting the one or more applications.</p> <p>For example, a container image has an associated image configuration comprising information for starting the one or more applications. This can be an Open Containers Initiative image configuration.</p> <p><i>See, e.g.:</i></p>



Claim 2	Accused Instrumentalities
	 <p>The diagram illustrates a container architecture stack. At the top, three application boxes labeled 'App 1' (green), 'App 2' (yellow), and 'App 3' (pink) are shown. Below each app is a corresponding 'Bins/Libs' box in the same color. These are all contained within a blue 'Container Runtime' box. This runtime sits on top of a white 'Host Operating System' box, which in turn sits on a grey 'Infrastructure' box. The entire stack is labeled 'Containers' at the bottom.</p> <p><a href="https://services.google.com/fh/files/misc/why_container_security_matters.pdf">https://services.google.com/fh/files/misc/why_container_security_matters.pdf</a></p> <h2>Open Container Initiative</h2> <hr/> <h3>Image Format Specification</h3> <hr/> <p>This specification defines an OCI Image, consisting of an <a href="#">image manifest</a>, an <a href="#">image index</a> (optional), a set of <a href="#">filesystem layers</a>, and a <a href="#">configuration</a>.</p> <p>The goal of this specification is to enable the creation of interoperable tools for building, transporting, and preparing a container image to run.</p> <p><a href="https://github.com/opencontainers/image-spec/blob/a6af2b480dcfc001ba975f44de53001c873cb0ef/spec.md">https://github.com/opencontainers/image-spec/blob/a6af2b480dcfc001ba975f44de53001c873cb0ef/spec.md</a></p>

Claim 2	Accused Instrumentalities
	<p data-bbox="638 250 816 289"><b>Overview</b></p> <p data-bbox="638 345 1877 586">At a high level the image manifest contains metadata about the contents and dependencies of the image including the content-addressable identity of one or more <a href="#">filesystem layer changeset</a> archives that will be unpacked to make up the final runnable filesystem. The image configuration includes information such as application arguments, environments, etc. The image index is a higher-level manifest which points to a list of manifests and descriptors. Typically, these manifests may provide different implementations of the image, possibly varying by platform or other attributes.</p> <div data-bbox="659 630 1898 1008"> <p>The diagram illustrates the components of an OCI image. On the left, a code block for a 'HelloWorld' class is shown. An arrow points from this code to a cylinder labeled 'layer' containing the paths '/bin/java', '/opt/app.jar', and '/lib/libc'. To the right of the layer is a plus sign, followed by a document icon labeled 'image index' containing a JSON snippet for 'manifests'. Another plus sign follows, leading to a document icon labeled 'config' containing a JSON snippet for 'config' with 'Cmd' set to ['java', '-jar', 'app.jar']. Each of these three components (layer, image index, and config) has a small OCI logo icon in its top-left corner.</p> <pre> public class HelloWorld {     public static void main(String[] args) {         System.out.println("Hello, World");     } } </pre> <pre> {   "manifests": {     "platform": {       "os": "linux",       ...     }   } } </pre> <pre> {   ...   "config": {     "Cmd": [       "java", "-jar",       "app.jar"     ],     ...   } } </pre> <p data-bbox="621 1036 1465 1105"> <a href="https://github.com/opencontainers/image-spec/blob/a6af2b480dcfc001ba975f44de53001c873cb0ef/spec.md">https://github.com/opencontainers/image-spec/blob/a6af2b480dcfc001ba975f44de53001c873cb0ef/spec.md</a> </p> </div>

Claim 2	Accused Instrumentalities
	<h2 data-bbox="638 245 1283 305">OCI Image Configuration</h2> <p data-bbox="638 358 1902 521">An OCI <i>Image</i> is an ordered collection of root filesystem changes and the corresponding execution parameters for use within a container runtime. This specification outlines the JSON format describing images for use with a container runtime and execution tool and its relationship to filesystem changesets, described in <a href="#">Layers</a>.</p> <p data-bbox="638 558 1646 591">This section defines the <code>application/vnd.oci.image.config.v1+json</code> <a href="#">media type</a>.</p> <p data-bbox="621 623 1493 695"><a href="https://github.com/opencontainers/image-spec/blob/a6af2b480dcfc001ba975f44de53001c873cb0ef/config.md">https://github.com/opencontainers/image-spec/blob/a6af2b480dcfc001ba975f44de53001c873cb0ef/config.md</a></p>

Claim 2	Accused Instrumentalities
	<ul style="list-style-type: none"> <li>• <b>config object</b>, OPTIONAL</li> </ul> <p>The execution parameters which SHOULD be used as a base when running a container using the image. This field can be <code>null</code> , in which case any execution parameters should be specified at creation of the container.</p> <ul style="list-style-type: none"> <li>◦ <b>Env array of strings</b>, OPTIONAL</li> </ul> <p>Entries are in the format of <code>VARNAME=VARVALUE</code> . These values act as defaults and are merged with any specified when creating a container.</p> <ul style="list-style-type: none"> <li>◦ <b>Entrypoint array of strings</b>, OPTIONAL</li> </ul> <p>A list of arguments to use as the command to execute when the container starts. These values act as defaults and may be replaced by an entrypoint specified when creating a container.</p> <ul style="list-style-type: none"> <li>◦ <b>Cmd array of strings</b>, OPTIONAL</li> </ul> <p>Default arguments to the entrypoint of the container. These values act as defaults and may be replaced by any specified when creating a container. If an <code>Entrypoint</code> value is not specified, then the first entry of the <code>Cmd</code> array SHOULD be interpreted as the executable to run.</p> <p><a href="https://github.com/opencontainers/image-spec/blob/a6af2b480dcfc001ba975f44de53001c873cb0ef/config.md">https://github.com/opencontainers/image-spec/blob/a6af2b480dcfc001ba975f44de53001c873cb0ef/config.md</a></p>

**Claim 4**

Claim 4	Accused Instrumentalities
<p>4. A method as defined in claim 1 further comprising the step of pre-identifying applications and system files required for association with the one or more containers prior to said storing step.</p>	<p>Google and/or its customer practices, through the Accused Instrumentalities, a method as defined in claim 1 further comprising the step of pre-identifying applications and system files required for association with the one or more containers prior to said storing step.</p> <p>For example, Google's Migrate to Containers feature identifies the application along with its dependencies to be migrated to the target cluster/container. This identification step happens before storing the containers having the migrated application and files in the target machine, as described above.</p> <p>See analysis and evidence for claim 1 above.</p> <p>See also, e.g.:</p> <p>The migration prerequisites are dependent on your specific migration environment. Confirm that your workloads' OS and source platform are compatible for migration by reviewing the prerequisites for your specific migration environment:</p> <p><a href="https://cloud.google.com/migrate/containers/docs/setting-up-overview">https://cloud.google.com/migrate/containers/docs/setting-up-overview</a></p> <p><b>Migrate data</b> </p> <p><a href="#">Send feedback</a></p> <p>This page describes how to run a data migration that copies files from the local machine to a persistent volume claim (PVC) in the target cluster.</p> <p><a href="https://cloud.google.com/migrate/containers/docs/m2c-cli/migrate-data">https://cloud.google.com/migrate/containers/docs/m2c-cli/migrate-data</a></p> <p><b>Copy the source machine's file system</b> </p> <p><a href="#">Send feedback</a></p> <p>Modernization of an application component requires creating a copy of the source machine's file system.</p> <p>This page describes the steps required to copy the source machine's file system along with some specifications for reducing the size of the copied file system.</p> <p><a href="https://cloud.google.com/migrate/containers/docs/m2c-cli/copy-file-system">https://cloud.google.com/migrate/containers/docs/m2c-cli/copy-file-system</a></p>

**Claim 6**

Claim 6	Accused Instrumentalities
<p>6. A method as defined in claim 2, comprising the step of assigning a unique associated identity to each of a plurality of the containers, wherein the identity includes at least one of IP address, host name, and MAC address.</p>	<p>Google and/or its customer practices, through the Accused Instrumentalities, a method as defined in claim 2, comprising the step of assigning a unique associated identity to each of a plurality of the containers, wherein the identity includes at least one of IP address, host name, and MAC address.</p> <p>For example, Kubernetes containers have an associated hostname, which in the case of a single-container Pod is the unique identity of that container. For another example, Kubernetes pods have an associated hostname, which is unique. For another example, a networked Kubernetes pod has an assigned IPv4 and/or IPv6 address. For another example, a Docker container has an IP address and a hostname.</p> <p><i>See, e.g.:</i></p> <h3>Container information</h3> <p>The <i>hostname</i> of a Container is the name of the Pod in which the Container is running. It is available through the <code>hostname</code> command or the <code>gethostname</code> function call in libc.</p> <p>The Pod name and namespace are available as environment variables through the <a href="#">downward API</a>.</p> <p>User defined environment variables from the Pod definition are also available to the Container, as are any environment variables specified statically in the container image.</p> <p><a href="https://kubernetes.io/docs/concepts/containers/container-environment/">https://kubernetes.io/docs/concepts/containers/container-environment/</a></p>



Claim 6	Accused Instrumentalities
	<h2 data-bbox="638 240 1234 293">IP address and hostname</h2> <p data-bbox="638 337 1896 461">By default, the container gets an IP address for every Docker network it attaches to. A container receives an IP address out of the IP subnet of the network. The Docker daemon performs dynamic subnetting and IP address allocation for containers. Each network also has a default subnet mask and gateway.</p> <p data-bbox="638 509 1877 678">You can connect a running container to multiple networks, either by passing the <code>--network</code> flag multiple times when creating the container, or using the <code>docker network connect</code> command for already running containers. In both cases, you can use the <code>--ip</code> or <code>--ip6</code> flags to specify the container's IP address on that particular network.</p> <p data-bbox="638 727 1883 857">In the same way, a container's hostname defaults to be the container's ID in Docker. You can override the hostname using <code>--hostname</code>. When connecting to an existing network using <code>docker network connect</code>, you can use the <code>--alias</code> flag to specify an additional network alias for the container on that network.</p> <p data-bbox="621 889 1050 919"><a href="https://docs.docker.com/network/">https://docs.docker.com/network/</a></p>

**Claim 9**

Claim 9	Accused Instrumentalities
<p data-bbox="201 1078 583 1399">9. A method as defined in claim 2, wherein server information related to hardware resource usage including at least one of CPU memory, network bandwidth, and disk allocation is associated with at least some of the containers prior to the</p>	<p data-bbox="621 1078 1913 1219">Google and/or its customer practices, through the Accused Instrumentalities, a method as defined in claim 2, wherein server information related to hardware resource usage including at least one of CPU memory, network bandwidth, and disk allocation is associated with at least some of the containers prior to the applications within the containers being executed.</p> <p data-bbox="621 1243 1919 1317">For example, Kubernetes tracks and limits resource usage, including CPU and memory resources. For another example, Docker tracks and limits resource usage, including CPU and memory resources.</p> <p data-bbox="621 1341 737 1370"><i>See, e.g.:</i></p>

Claim 9	Accused Instrumentalities
applications within the containers being executed.	<p data-bbox="716 235 1472 272"><b><u>Resource Management for Pods and Containers</u></b></p> <p data-bbox="716 316 1913 435">When you specify a <u>Pod</u>, you can optionally specify how much of each resource a <u>container</u> needs. The most common resources to specify are CPU and memory (RAM); there are others.</p> <p data-bbox="716 483 1923 732">When you specify the resource <i>request</i> for containers in a Pod, the <u>kube-scheduler</u> uses this information to decide which node to place the Pod on. When you specify a resource <i>limit</i> for a container, the <u>kubelet</u> enforces those limits so that the running container is not allowed to use more of that resource than the limit you set. The kubelet also reserves at least the <i>request</i> amount of that system resource specifically for that container to use.</p> <p data-bbox="716 781 1031 818">Requests and limits</p> <p data-bbox="716 829 1906 987">If the node where a Pod is running has enough of a resource available, it's possible (and allowed) for a container to use more resource than its <i>request</i> for that resource specifies. However, a container is not allowed to use more than its resource <i>limit</i>.</p> <p data-bbox="716 1036 1856 1154">For example, if you set a <i>memory request</i> of 256 MiB for a container, and that container is in a Pod scheduled to a Node with 8GiB of memory and no other Pods, then the container can try to use more RAM.</p> <p data-bbox="716 1203 1917 1365">If you set a <i>memory limit</i> of 4GiB for that container, the kubelet (and <u>container runtime</u>) enforce the limit. The runtime prevents the container from using more than the configured resource limit. For example: when a process in the container tries to consume more than the allowed amount of memory, the system kernel</p>

Claim 9	Accused Instrumentalities
	<p>terminates the process that attempted the allocation, with an out of memory (OOM) error.</p> <p>Limits can be implemented either reactively (the system intervenes once it sees a violation) or by enforcement (the system prevents the container from ever exceeding the limit). Different runtimes can have different ways to implement the same restrictions.</p> <p><a href="https://kubernetes.io/docs/concepts/configuration/manage-resources-containers/">https://kubernetes.io/docs/concepts/configuration/manage-resources-containers/</a></p> <p><b>Runtime options with Memory, CPUs, and GPUs</b></p> <p>By default, a container has no resource constraints and can use as much of a given resource as the host's kernel scheduler allows. Docker provides ways to control how much memory, or CPU a container can use, setting runtime configuration flags of the <code>docker run</code> command. This section provides details on when you should set such limits and the possible implications of setting them.</p> <p><b>Limit a container's access to memory</b></p> <p>Docker can enforce hard or soft memory limits.</p> <ul style="list-style-type: none"> <li>• Hard limits lets the container use no more than a fixed amount of memory.</li> <li>• Soft limits lets the container use as much memory as it needs unless certain conditions are met, such as when the kernel detects low memory or contention on the host machine.</li> </ul> <p><a href="https://docs.docker.com/config/containers/resource_constraints/">https://docs.docker.com/config/containers/resource_constraints/</a></p>


**Claim 10**

<b>Claim 10</b>	<b>Accused Instrumentalities</b>
<p>10. A method as defined in claim 2, wherein in operation when an application residing within a container is executed, said application has no access to system files or applications in other containers or to system files within the operating system during execution thereof.</p>	<p>Google and/or its customer practices, through the Accused Instrumentalities, a method as defined in claim 2, wherein in operation when an application residing within a container is executed, said application has no access to system files or applications in other containers or to system files within the operating system during execution thereof.</p> <p><i>See, e.g.:</i></p> <p>Containers solve the portability problem by isolating the application and its dependencies so they can be moved seamlessly between machines. A process running in a container lives isolated from the underlying environment. You control what it can see and what resources it can access. This helps you use resources more efficiently and not worry about the underlying infrastructure.</p> <p>One of the primary reasons to adopt containers is for your applications to be decoupled from the underlying environment and support higher resource utilization by “bin packing” multiple workloads onto each server. As such, the architecture of containers means that they’re deployed with multiple containers sharing the same kernel.</p> <p>Containers use primitives of the Linux kernel (cgroups, namespaces) to isolate processes in an environment</p> <p><a href="https://services.google.com/fh/files/misc/why_container_security_matters.pdf">https://services.google.com/fh/files/misc/why_container_security_matters.pdf</a></p>

Claim 10	Accused Instrumentalities
	<p>The core components of the Linux kernel that are used for containers are <b>cgroups</b> — control groups, which define the resources like CPU and memory which are available to a given process — and <b>namespaces</b>, which are a way of separating processes by restricting what each process can see, so that system resources “appear” isolated to the process.</p> <p><a href="https://services.google.com/fh/files/misc/why_container_security_matters.pdf">https://services.google.com/fh/files/misc/why_container_security_matters.pdf</a></p>



**Claim 13**

Claim 13	Accused Instrumentalities
<p>13. A method as defined in claim 1 further comprising the step of associating with a plurality of containers a stored history of when processes related to applications within the container are executed for at least one of, tracking statistics, resource allocation, and for monitoring the status of the application.</p>	<p>Google and/or its customer practices, through the Accused Instrumentalities, a method as defined in claim 1 further comprising the step of associating with a plurality of containers a stored history of when processes related to applications within the container are executed for at least one of, tracking statistics, resource allocation, and for monitoring the status of the application.</p> <p><i>See analysis and evidence for claim 1 above.</i></p> <p><i>See also, e.g.:</i></p> <ul style="list-style-type: none"> <li>• <b>Logging, monitoring, and tracing.</b> Capture information on your monitoring, logging, and tracing systems. You can integrate your systems with the <a href="#">Google Cloud Observability</a>, or you can use Google Cloud Observability as your only monitoring, logging, and tracing tool. For example, you can <a href="#">integrate Google Cloud Observability with other services</a>, set up <a href="#">logging interfaces for your preferred programming languages</a>, and use the <a href="#">Cloud Logging agent on your VMs</a>. GKE integrates with <a href="#">Google Cloud Observability</a> and <a href="#">Cloud Audit Logs</a>. You can also <a href="#">customize Cloud Logging logs for GKE with Fluentd</a> and then process logs at scale using Dataflow.</li> </ul> <p><a href="https://cloud.google.com/architecture/migrating-containers-kubernetes-gke">https://cloud.google.com/architecture/migrating-containers-kubernetes-gke</a></p>

Claim 13	Accused Instrumentalities
	 <p><a href="https://cloud.google.com/blog/products/gcp/manage-google-kubernetes-engine-from-cloud-console-dashboard-now-generally-available">https://cloud.google.com/blog/products/gcp/manage-google-kubernetes-engine-from-cloud-console-dashboard-now-generally-available</a></p>

**Claim 14**

Claim 14	Accused Instrumentalities
<p>14. A method as defined in claim 1 comprising the step of creating containers prior to said step of storing containers in memory, wherein containers are created by:</p>	<p>Google and/or its customer practices, through the Accused Instrumentalities, a method as defined in claim 1 comprising the step of creating containers prior to said step of storing containers in memory, wherein containers are created by (a) running an instance of a service on a server; (b) determining which files are being used; and, (c) copying applications and associated system files to memory without overwriting the associated system files so as to provide a second instance of the applications and associated system files.</p>

Claim 14	Accused Instrumentalities
<p>a) running an instance of a service on a server;  b) determining which files are being used; and,  c) copying applications and associated system files to memory without overwriting the associated system files so as to provide a second instance of the applications and associated system files.</p>	<p>For example, GKE, Cloud Run, and Migrate to Containers support the creation of containers and deploying the containers on the server. The containers are first created and then later deployed/stored on the server. The creation step involves determining which applications and files are to be migrated, copying these identified applications and files to a location in the target server. Based on information and belief, once the files are migrated, the earlier stored files (if any) are not deleted/overwritten, rather, the migrated files are stored as different instance in memory accessible to containers. Further, an instance of an application/service may be tested or run on the target server to ensure compatibility.</p> <p><i>See analysis and evidence for claim 1 above.</i></p> <p><i>See also, e.g.:</i></p> <p><b>Migrate data</b> </p> <p>This page describes how to run a data migration that copies files from the local machine to a persistent volume claim (PVC) in the target cluster.</p> <p><a href="https://cloud.google.com/migrate/containers/docs/m2c-cli/migrate-data">https://cloud.google.com/migrate/containers/docs/m2c-cli/migrate-data</a></p> <p><b>Copy the source machine's file system</b> </p> <p>Modernization of an application component requires creating a copy of the source machine's file system.</p> <p>This page describes the steps required to copy the source machine's file system along with some specifications for reducing the size of the copied file system.</p> <p><a href="https://cloud.google.com/migrate/containers/docs/m2c-cli/copy-file-system">https://cloud.google.com/migrate/containers/docs/m2c-cli/copy-file-system</a></p> <p>The migration prerequisites are dependent on your specific migration environment. Confirm that your workloads' OS and source platform are compatible for migration by reviewing the prerequisites for your specific migration environment:</p> <p><a href="https://cloud.google.com/migrate/containers/docs/setting-up-overview">https://cloud.google.com/migrate/containers/docs/setting-up-overview</a></p>